

Product information GDME LED 24 RD

| Industrial Connectors:Rectangular connectors GDM-series:Type A EN 175301-803 (DIN 43650) / ISO 4400:Electronic inserts for GDME:GDME LED 24 RD | |
|--|--|
| http://e-catalog.beldensolutions.com/link/57078-24228-24309-24310-24315-35670/en/conf/uistate | |
| Name | GDME LED 24 RD |
| | |
| | function indicator (LED) with freewheeling diode |
| Delivery informations | |
| Availability | available |
| Product description Description | function indicator (LED) with freewheeling diode |
| Туре | GDME LED 24 RD |
| Order No. | 831 839-001 |
| Standard | DIN EN 175 301-803-A |
| Construction type | A |
| Description of Wiring | |
| LED color | LED red |
| Technical data | |
| Rated voltage | AC/DC 24 V |
| Rated current | 8 A |
| Environmental conditions | |
| Temperature range | -40 °C to +110 °C |
| Packing unit | |
| Packaging unit | 50 pieces |
| Picture | |
| Drawing | $(\underline{v}) \circ (\underline{v})_{1}$ $(\underline{v}) \circ (\underline{v})_{2}$ $(\underline{v}) \circ (\underline{v})_{2}$ $(\underline{v}) \circ (\underline{v})_{2}$ $(\underline{v}) \circ (\underline{v})_{2}$ $(\underline{v}) \circ (\underline{v})_{2}$ |

Belden Wire and Cable BV Edisonstraat 9 5928 PG Venlo The Netherlands Phone: +31 773878 287 E-Mail: Elisabeth.Eufinger-Nagels@belden.com







The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on data sheets and user documentation. Mandatory information can only be obtained by a concrete query.



